

Part#	Description	Price
Sun Fire X2200		
A85-ZSZ2-H-8GC-JL8	Sun Fire X2200 M2 x64 Server: 2x Quad Core AMD Opteron Model 2376 processors (2.3GHz/6MB L3/75W ACP), 4x 2GB registered ECC single rank DDR2-667 memory, no hard drives, no optical drive, 1x PSU, Service Processor, 4x 10/100/1000 Ethernet ports, 6x USB 2.0 ports, 1x I/O riser card with 2x PCI-Express x8 slots, no power cords, order Geo-specific x-option. RoHS-5. Standard Configuration.	284 500 Ft
A85-ZWZ2-H-8GC-JL8	Sun Fire X2200 M2 x64 Server: 2x Quad Core AMD Opteron Model 2384 processors (2.7GHz/6MB L3/75W ACP), 4x 2GB registered ECC single rank DDR2-667 memory, no hard drives, no optical drive, 1x PSU, Service Processor, 4x 10/100/1000 Ethernet ports, 6x USB 2.0 ports, 1x I/O riser card with 2x PCI-Express x8 slots, no power cords, order Geo-specific x-option. RoHS-5. Standard Configuration.	425 200 Ft
XRC-ST1CE-250G7K	X-Option Internal 250GB 7,200 RPM 3.5-inch Serial ATA Hard Disk Drive with bracket. RoHS-6.	20 500 Ft
XRB-ST1CE-500G7K	X-Option Internal 500GB 7,200 RPM 3.5-inch Serial ATA Hard Disk Drive with bracket. RoHS-6.	25 300 Ft
XRB-ST1CE-1T7K	Internal 3.5-inch 1TB 7200 rpm Serial ATA Hard Disk Drive with bracket. X-option. RoHS-6.	38 600 Ft
XRB-SS1CE-146G15KZ	RoHS-6. Internal 146GB 15K SAS HDD, 3.5" x 1" drive with bracket.	38 500 Ft
XRB-SS1CE-300G15K	RoHS-6. Internal 300GB 15K SAS HDD, 3.5" x 1" drive with bracket.	61 600 Ft
X8029A-Z	X2100/X4100/X4200: Slide rail	14 300 Ft
X4446A-Z	Sun x4 PCI Express Quad Gigabit Ethernet UTP low profile adapter, low profile bracket on board, standard bracket included. RoHS-6 compliant, IntelOEM card	69 900 Ft
X5286A-Z	X-Option DVD+/-RW Dual Layer (DL) drive for Sun Fire X2100 M2 and Sun Fire X2200 M2 x64 servers. RoHS-6.	27 800 Ft
SG-XPCIE4SAS3-Z	4 x1 4-Port SAS PCI-E HBA internal connection LSI3041E with B3 silicon X-Option. RoHS-6 compliant.	46 100 Ft
SGXPCIESAS-R-EXT-Z	Sun StorageTek (TM) 8-port external SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. X-Option.	90 300 Ft
X5295A-Z	SAS Drive Cable Kit for Sun Fire X2200 M2 servers. Two cables (750mm; 400mm). ROHS-5. X-Option.	2 300 Ft
X5288A-C	X-Option 4-GB Memory Kit (2x 2GB Registered ECC single rank DDR2-667) for Sun Fire X2200 M2 server. RoHS-6.	21 700 Ft
X5294A-Z	X-Option DVD-ROM drive for Sun Fire X2100 M2 and Sun Fire X2200 M2 x64 servers. RoHS-5.	18 200 Ft
X7280A-2	Sun PCI-E Low profile Dual GigE UTP, low profile bracket on board, standard bracket included. RoHS-6 compliant	62 600 Ft

Part#	Description	Price
Sun Fire X2250		
X2250-14-M200-22-A	Sun Fire X2250 x64 Rack-Mount Server. One Quad Core Intel Xeon E5405 (12MB L2, 2.00GHz, 1333MHz FSB, 80W) 4GB (2x 2GB, 667MHz Fully-buffered DIMM), No HDD, no DVD, 1x PSU, ILOM, 2x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 1x 16-lane PCI-Express slot, no power cord, order geo-specific x-option. Standard Configuration. RoHS-5. Optional Media and Documentation Kit (Installation Guide, Tools & Drivers CD, Sun Installation Assistant CD, SMI SW Licensing Agreement.)	287 000 Ft
X2250-14-L250-22-A	SunFireX2250 x64 Rack-Mount Server:1x Quad-Core Intel Xeon L5420 processor (12MB L2, 2.50 GHz,1333 MHz FSB, 50W), 4GB mem (2X2GB ECC,DDR2-667 FB-DIMM), No HDD,no DVD,1x PSU,ILOM, 4x 10/100/1000 Ethernet ports,5xUSB 2.0 ports,1x 16-lane PCI-Express slot, no powercord, order Geo-specific x-option. Standard Config. RoHS-5. Optional Media and Doc Kit (Installation Guide, Tools & Drivers CD, Sun Installation Assistant CD, SMI SW Licensing Agreement.)	339 100 Ft
X2250-14-H300-24-A	Sun Fire X2250 Rack-Mount Server: 1x Quad-Core Intel Xeon X5472 processor (12MB L2, 3.0GHz, 1600MHz FSB, 120W), 8GB memory (2X4 GB 800MHz FBDIMM), No HDD, no DVD, 1x PSU, ILOM, 2x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 1x 16-lane PCI-Express slot, no power cord, order geo-specific x-option. Standard Configuration. RoHS-5. Optional Media and Documentation Kit (Installation Guide, Tools & Drivers CD, Sun Installation Assistant CD, SMI SW Licensing Agreement.)	521 700 Ft
XRC-ST1CE-250G7K	X-Option Internal 250GB 7,200 RPM 3.5-inch Serial ATA Hard Disk Drive with bracket. RoHS-6.	20 500 Ft
XRБ-ST1CE-500G7K	X-Option Internal 500GB 7,200 RPM 3.5-inch Serial ATA Hard Disk Drive with bracket. RoHS-6.	25 300 Ft
XRБ-ST1CE-1T7K	Internal 3.5-inch 1TB 7200 rpm Serial ATA Hard Disk Drive with bracket. X-option. RoHS-6.	38 600 Ft
X8029A-Z	X2100/X4100/X4200: Slide rail	14 300 Ft
X6381A	4GB Memory Kit with 2x2GB PC2-5300 667 MHz ECC Fully Buffered DDR2 DIMM. RoHS-6. X-Option.	21 400 Ft
X5111A	4GB Memory Kit for Sun Fire X2250 with 2x2GB 800MHz PC2-6400 ECC Fully Buffered DIMM. RoHS-5. X-option.	48 600 Ft
X6382A	8GB Memory Kit with 2x4GB PC2-5300 667 MHz ECC Fully Buffered DDR2 DIMM for Sun Fire and Netra X4150, X4250 and X4450. RoHS-6. X-Option.	44 300 Ft
X5110A	8GB Memory Kit for Sun Fire X2250 with 2x4GB 800MHz PC2-6400 ECC Fully Buffered DIMM. RoHS-5. X-option.	96 500 Ft
X4446A-Z	Sun x4 PCI Express Quad Gigabit Ethernet UTP low profile adapter, low profile bracket on board, standard bracket included. RoHS-6 compliant, IntelOEM card	69 900 Ft
X5113A	Sun Fire X2250 Quad Core Intel Xeon Processor Model L5420 (2.50GHz, 1333MHz FSB, 50W), ROHS-5.	117 400 Ft

Part#	Description	Price
X5294A-Z	X-Option DVD-ROM drive for Sun Fire X2100 M2 and Sun Fire X2200 M2 x64 servers. RoHS-5.	18 200 Ft
X5109A	Intel Xeon E5405 Quad Core (6MB L2, 2.0 GHz, 1333 MHz FSB, 80W)	67 800 Ft
X5286A-Z	X-Option DVD+/-RW Dual Layer (DL) drive for Sun Fire X2100 M2 and Sun Fire X2200 M2 x64 servers. RoHS-6.	27 800 Ft
Sun Fire X4150		
B13-UE2-EC-8GB-KD6	Sun Fire X4150 x64 Rack-Mount Server: Two Quad-Core Intel(R) Xeon(R) X5460 processor (2x6MB L2, 3.16 GHz, 1333 MHz FSB, 120W), 8GB of memory (4x2GB PC2-5300 667 MHz ECC fully buffered DDR2 DIMMs), 4x 146GB 10K RPM 2.5? SAS drives, internal SAS RAID PCI-Express HBA, DVD+/-RW drive, 2x PSU, ILOM, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 3x 8-lane PCI-Express slots, no power cord, order Geo-specific X-option. Solaris 10 and Java ES preinstall. Standard Configuration. RoHS-5.	1 408 700 Ft
B13-US1-CC-4GF-JLB	Sun Fire X4150 x64 Rack-Mount Server: One Quad-Core Intel Xeon E5410 processor (2x6MB L2, 2.33 GHz, 1333 MHz FSB, 80W), 4GB of memory (2x 2GB PC2-5300 667 MHz ECC fully buffered DDR2 DIMMs), no HDD, no DVD, 1x PSU, ILOM, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 3x 8-lane PCI-Express slots, no power cord, order Geo-specific x-option. Standard Configuration. RoHS-5.	403 000 Ft
B13-UQ2-CC-8GB-KD6	Sun Fire X4150 x64 Rack-Mount Server: Two Quad-Core Intel Xeon E5450 processor (2x6MB L2, 3.0 GHz, 1333 MHz FSB, 80W), 8GB memory (4x 2GB PC2-5300 667 MHz ECC fully buffered DDR2 DIMMs), 4x 146GB 10K RPM 2.5 SAS drives, SAS RAID HBA, DVD-RW, 2x PSU, ILOM, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 3x 8-lane PCI-Express slots, no power cord, order Geo-specific x-option. Solaris 10 & Java ES pre-installed. Standard Configuration. RoHS-5.	1 330 400 Ft
X6326A	Slide rail kit for Sun Fire X4140/X4170/X4270/X4440/X4150/X4450 server. Only fits in Sun Rack 938, Sun Rack 1038, Sun Rack 1042, or racks that have front to rear rail spacing between 610mm and 915mm (about 24" to about 36"). RoHS-6. X-option.	14 500 Ft
XRB-SS2CD-146G10K	146GB 10K RPM 2.5" SAS hard disk drive with Nemo bracket. RoHS-6 Compliant. (x-option)	36 300 Ft
XRA-ST2CF-32G2SSD	2.5? 32GB SATA SSD (Type: SLC) with Marlin bracket, X-option RoHS-6	121 900 Ft
XRA-SS2CF-73G15K	73GB 15K RPM 2.5? SAS disk drive with Marlin bracket. RoHS-6. X-Option.	48 900 Ft
XRA-SS2CF-300G10K	300GB 10K RPM 2.5? SAS hard disk drive with Marlin bracket. (x-option) RoHS-6	65 700 Ft
SG-XPCIE8SAS-E-Z	Sun StorageTek (TM) 8-port external SAS PCI-Express Host Bus Adapter. RoHS 6. X-option	41 900 Ft
X6327A	Redundant hot-swappable AC 650W power supply unit for Sun Fire X4140 and X4150 server. RoHS-5. X-option.	47 000 Ft
X6381A	4GB Memory Kit with 2x2GB PC2-5300 667 MHz ECC Fully Buffered DDR2 DIMM. RoHS-6. X-Option.	21 400 Ft

Part#	Description	Price
X6323A	DVD+/-RW drive for Sun Fire X4150/X4250/X4450/X4140/X4240/X4440 server. RoHS-5. X-Option.	27 800 Ft
X6388A	Internal SAS Drive Cable Kit for Sun Fire X4150 server. ROHS-5. X-option.	2 900 Ft
SG-PCIE8SAS-I-Z	Sun StorageTek (TM) 8-Port internal SAS PCI-Express LSI 3081E Host Bus Adapter with RAID 0, 1, 1E support. RoHS-6. XATO.	57 400 Ft
SGXPCIESAS-R-INT-Z	Sun StorageTek (TM) 8-port internal SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. X-Option.	74 400 Ft
X6382A	8GB Memory Kit with 2x4GB PC2-5300 667 MHz ECC Fully Buffered DDR2 DIMM for Sun Fire and Netra X4150, X4250 and X4450. RoHS-6. X-Option.	44 300 Ft
Sun Fire X4250		
X425-14L250-22AE	Sun Fire X4250 x64 Rack-Mount Server: One Quad-Core Intel Xeon L5420 processor (2x6MB L2, 2.50 GHz, 1333 MHz FSB, 50W), 4GB of memory (2x 2GB PC2-5300 667 MHz ECC fully buffered DDR2 DIMMs), no HDD, SATA-based DVD+/-RW, 1x PSU, ILOM, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 6x PCI-Express slots, no power cord, order Geo-specific x-option. Standard Configuration. RoHS-5.	665 200 Ft
X425-24H316-42EE	Sun Fire X4250 x64 Rack-Mount Server: Two Quad-Core Intel Xeon X5460 processor (2x6MB L2, 3.16 GHz, 1333 MHz FSB, 120W), 8GB of memory (4x 2GB PC2-5300 667 MHz ECC fully buffered DDR2 DIMMs), 4x 146GB 10000 rpm 2.5-inch SAS drives, SAS RAID HBA, SATA-based DVD+/-RW, 2x PSU, ILOM, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 6x PCI-Express slots, no power cord, order Geo-specific x-option. Standard Configuration. RoHS-5.	1 539 100 Ft
X425-24M300-42EE	Sun Fire X4250 x64 Rack-Mount Server: Two Quad-Core Intel Xeon E5450 processor (2x6MB L2, 3.0 GHz, 1333 MHz FSB, 80W), 8GB of memory (4x 2GB PC2-5300 667 MHz ECC fully buffered DDR2 DIMMs), 4x 146GB 10000 rpm 2.5-inch SAS drives, SAS RAID HBA, SATA-based DVD+/-RW, 2x PSU, ILOM, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 6x PCI-Express slots, no power cord, order Geo-specific x-option. Standard Configuration. RoHS-5.	1 460 900 Ft
XRB-SS2CD-146G10K	146GB 10K RPM 2.5" SAS hard disk drive with Nemo bracket. RoHS-6 Compliant. (x-option)	36 300 Ft
XRA-ST2CF-32G2SSD	2.5" 32GB SATA SSD (Type: SLC) with Marlin bracket, X-option RoHS-6	121 900 Ft
XRA-SS2CF-300G10K	300GB 10K RPM 2.5" SAS hard disk drive with Marlin bracket. (x-option) RoHS-6	65 700 Ft
SG-PCIE8SAS-I-Z	Sun StorageTek (TM) 8-Port internal SAS PCI-Express LSI 3081E Host Bus Adapter with RAID 0, 1, 1E support. RoHS-6. XATO.	57 400 Ft
SGXPCIESAS-R-INT-Z	Sun StorageTek (TM) 8-port internal SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. X-Option.	74 400 Ft

Part#	Description	Price
X6382A	8GB Memory Kit with 2x4GB PC2-5300 667 MHz ECC Fully Buffered DDR2 DIMM for Sun Fire and Netra X4150, X4250 and X4450. RoHS-6. X-Option.	44 300 Ft
X6327A	Redundant hot-swappable AC 650W power supply unit for Sun Fire X4140 and X4150 server. RoHS-5. X-option.	47 000 Ft
X6381A	4GB Memory Kit with 2x2GB PC2-5300 667 MHz ECC Fully Buffered DDR2 DIMM. RoHS-6. X-Option.	21 400 Ft
X6323A	DVD+/-RW drive for Sun Fire X4150/X4250/X4450/X4140/X4240/X4440 server. RoHS-5. X-Option.	27 800 Ft
Sun Fire X4450		
B15-WZ4-FC-16G-KD6	Sun Fire X4450 x64 Rack-Mount Server: 4x Quad-Core Intel(R) Xeon(R) X7350 processor (2x4MB L2, 2.93GHz, 1066 MHz FSB, 130W), 16GB of memory (8x2GB PC2-5300 667 MHz ECC fully buffered DDR2 DIMMs), 4x 146GB 10K RPM 2.5 SAS disk drives, internal SAS RAID HBA, DVD+/-RW drive, 2x 1100W PSU, Embedded LOM, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 6x PCI-E slots, no power cord, order Geo-specific x-option. Solaris 10 & Java ES pre-installed,accessory kit, doc, CD's. RoHS-5.	4 121 700 Ft
B15-WZ2-FC-4GB-JL6	Sun Fire X4450 x64 Rack-Mount Server: Two Quad-Core Intel Xeon X7350 processor (2x4MB L2, 2.93 GHz, 1066 MHz FSB, 130W), 4GB of memory (2x2GB PC2-5300 667 MHz EEC fully buffered DDR2 DIMM), no HDD, DVD+/-RW, 1x 1100W PSU, ILOM, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 6x PCI-Express slots, no media & doc kit, no power cord, order Geo-specific x-option. Standard Configuration. RoHS-5.	2 191 300 Ft
B15-VZ4-CB-8GB-JL6	Sun Fire X4450 x64 Rack-Mount Server: 4x Dual-Core Intel(R) Xeon(R) E7220 processor (2x4MB L2, 2.93 GHz, 1066 MHz FSB, 80W), 8GB memory (8x1GB PC2-5300 667 MHz ECC fully buffered DDR2 DIMMs), no HDD, DVD+/-RW drive, 2x 1050W PSU, Embedded LOM, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 6x PCI-E slots, no power cord, order Geo-specific x-option. standard accessory kit, documentation, CD's. Standard configuration. RoHS-5.	2 478 300 Ft
B15-VW4-AC-8GB-JL6	Sun Fire X4450 x64 Rack-Mount Server: 4x Quad-Core Intel(R) Xeon(R) L7345 processor (2x4MB L2, 1.86 GHz, 1066 MHz FSB, 50W), 8GB memory (8x1GB PC2-5300 667 MHz ECC fully buffered DDR2 DIMMs), no HDD, DVD+/-RW drive, 2x 1050W PSU, Embedded LOM, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 6x PCI-E slots, no power cord, order Geo-specific x-option. Standard accessory kit, documentation, CD's. Standard configuration. RoHS-5.	3 704 400 Ft

Part#	Description	Price
B15-VR2-CC-4GB-JL6	Sun Fire X4450 x64 Rack-Mount Server: 2x Quad-Core Intel(R) Xeon(R) E7320 processor (2x2MB L2, 2.13 GHz, 1066 MHz FSB, 80W), 4GB memory (4x1GB PC2-5300 667 MHz ECC fully buffered DDR2 DIMMs), no HDD, DVD+/-RW drive, 1x 1050W PSU, Embedded LOM, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 6x PCI-E slots, no power cord, order Geo-specific x-option. Standard accessory kit, documentation, CD's. Standard configuration. RoHS-5.	1 591 300 Ft
B15-VJ4-CC-16G-KD6	Sun Fire X4450 x64 Rack-Mount Server: 4x Quad-Core Intel(R) Xeon(R) E7340 processors (2x4MB L2, 2.40 GHz, 1066 MHz FSB, 80W), 16 GB memory (8x2GB PC2-5300 667 MHz ECC fully buffered DDR2 DIMMs), 4x 146GB 10K RPM 2.5" SAS HDD, internal SAS RAID HBA, DVD +/-RW drive, 2x 1050W PSU, Embedded LOM, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 6x PCI-E slots, no power cord, order geo-specific x-option. Solaris 10 & Java ES pre-installed, std accessory kit, doc, CD's. Std Config. RoHS-5.	3 808 700 Ft
B15-VJ2-CC-4GB-JL6	Sun Fire X4450 x64 Rack-Mount Server: Two Quad-Core Intel Xeon E7340 processor (2x4MB L2, 2.40 GHz, 1066 MHz FSB, 80W), 4GB of memory (2x2GB PC2-5300 667 MHz EEC fully buffered DDR2 DIMM), no HDD, DVD+/-RW, 1x 1100W PSU, ILOM, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 6x PCI-Express slots, no media & doc kit, no power cord, order Geo-specific x-option. Standard Configuration. RoHS-5.	2 034 800 Ft
X6326A	Slide rail kit for Sun Fire X4140/X4170/X4270/X4440/X4150/X4450 server. Only fits in Sun Rack 938, Sun Rack 1038, Sun Rack 1042, or racks that have front to rear rail spacing between 610mm and 915mm (about 24" to about 36"). RoHS-6. X-option.	14 500 Ft
X6381A	4GB Memory Kit with 2x2GB PC2-5300 667 MHz ECC Fully Buffered DDR2 DIMM. RoHS-6. X-Option.	21 400 Ft
X6323A	DVD+/-RW drive for Sun Fire X4150/X4250/X4450/X4140/X4240/X4440 server. RoHS-5. X-Option.	27 800 Ft
SG-PCIE8SAS-I-Z	Sun StorageTek (TM) 8-Port internal SAS PCI-Express LSI 3081E Host Bus Adapter with RAID 0, 1, 1E support. RoHS-6. XATO.	57 400 Ft
SGXPCIESAS-R-INT-Z	Sun StorageTek (TM) 8-port internal SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. X-Option.	74 400 Ft
XRB-SS2CD-146G10K	146GB 10K RPM 2.5" SAS hard disk drive with Nemo bracket. RoHS-6 Compliant. (x-option)	36 300 Ft
Sun Fire X4140		
B12-AW1-DC-4C-JL8	Sun Fire X4140 x64 Server: 1x AMD Opteron Model 2384 (2.7GHz/512KB) quad core processor, 2x 2GB DDR2-667 single rank memory, No HDD, No DVD1RW, 1x PSU, HT Bridge Card, Service processor, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 1x 16-lane PCIe slot, 2x 8-lane PCIe slots, no Power Cord, order Geo-specific X-option. Standard Configuration. RoHS-5.	560 900 Ft

Part#	Description	Price
B12-AT2-DC-8C-RD6	Sun Fire X4140 x64 Server: 2x AMD Opteron Model 2380 (2.5GHz/512KB) quad core processor, 4x 2GB DDR2-667 single rank memory, 4x 146GB HDD, HBA RAID Card, DVD-RW, 2x PSU, HT Bridge Card, Service processor, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 1x 16-lane PCIe slot, 2x 8-lane PCIe slots, no Power Cord, order Geo-specific X-option. Solaris 10 Pre-Install. Standard Configuration. RoHS-5.	1 069 600 Ft
B12-AW2-DC-8C-RD6	Sun Fire X4140 x64 Server: 2x AMD Opteron Model 2384 (2.7GHz/512KB) quad core processor, 4x 2GB DDR2-667 single rank memory, 4x 146GB HDD, HBA RAID Card, DVD-RW, 2x PSU, HT Bridge Card, Service processor, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 1x 16-lane PCIe slot, 2x 8-lane PCIe slots, no Power Cord, order Geo-specific X-option. Solaris 10 Pre-Install. Standard Configuration. RoHS-5.	1 173 900 Ft
X6326A	Slide rail kit for Sun Fire X4140/X4170/X4270/X4440/X4150/X4450 server. Only fits in Sun Rack 938, Sun Rack 1038, Sun Rack 1042, or racks that have front to rear rail spacing between 610mm and 915mm (about 24" to about 36"). RoHS-6. X-option.	14 500 Ft
XRB-SS2CD-146G10K	146GB 10K RPM 2.5" SAS hard disk drive with Nemo bracket. RoHS-6 Compliant. (x-option)	36 300 Ft
XRA-SS2CF-300G10K	300GB 10K RPM 2.5" SAS hard disk drive with Marlin bracket. (x-option) RoHS-6	65 700 Ft
XRA-ST2CF-32G2SSD	2.5" 32GB SATA SSD (Type: SLC) with Marlin bracket, X-option RoHS-6	121 900 Ft
X4446A-Z	Sun x4 PCI Express Quad Gigabit Ethernet UTP low profile adapter, low profile bracket on board, standard bracket included. RoHS-6 compliant, IntelOEM card	69 900 Ft
X6327A	Redundant hot-swappable AC 650W power supply unit for Sun Fire X4140 and X4150 server. RoHS-5. X-option.	47 000 Ft
X6321A-C	X-Option 4 GB Memory kit DDR2-667 Registered ECC single rank DIMMs (2x 2GB) for Sun Fire X4140/X4240/X4440 x64 servers. RoHS-5.	48 600 Ft
X6323A	DVD+/-RW drive for Sun Fire X4150/X4250/X4450/X4140/X4240/X4440 server. RoHS-5. X-Option.	27 800 Ft
SG-PCIE8SAS-I-Z	Sun StorageTek (TM) 8-Port internal SAS PCI-Express LSI 3081E Host Bus Adapter with RAID 0, 1, 1E support. RoHS-6. XATO.	57 400 Ft
SGXPCIESAS-R-INT-Z	Sun StorageTek (TM) 8-port internal SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. X-Option.	74 400 Ft
XRA-SS2CF-73G15K	73GB 15K RPM 2.5" SAS disk drive with Marlin bracket. RoHS-6. X-Option.	48 900 Ft
Sun Fire X4600		

Part#	Description	Price
A67-ZWZ8-8H-064LB1	Sun Fire X4600 M2 x64 server: 8xAMD Opteron Model 8384 processor (2.7GHz-ACP75W-quad-core-8DIMM), 16x4GB DDR2-667 memory, 2x146 GB SAS drive, DVD-ROM, 4x1133W/higher PSU, Service Processor, 4x10/100/1000 BaseT Ethernet ports, 4xUSB 2.0 ports, 2xPCI-X slots, 6x PCI-E slots(4x8-lane, 2x4-lane), and sliderail kit. No power cord, must order Geo-specific power cord option.RoHS-5. Standard Configuration.	7 278 300 Ft
A67-ZZZ4-8H-16CLB1	Sun Fire X4600 M2 Server, 4 Quad-Core AMD Opteron Model 8389, (2.9GHz/512KB), 16GB (8x2GB) DDR2-667 Single-Rank memory, 2x146 GB 10000 rpm SAS drive, DVD-ROM, 4 1133W Power Supply Units, Service Processor, 4x10/100/1000 Ethernet ports, 4 USB 2.0 ports, 2 PCI-X slots, 4 x8-lane PCIe slot, 2 x4-lane PCIe slot, and sliderail kit. No power cord, must order Geo-specific power cord option.RoHS-5 compliant.	4 982 600 Ft
A67-ZZZ8-8H-064LB1	Sun Fire X4600 M2 Server, 8 Quad-Core AMD Opteron Model 8389, (2.9GHz/512KB), 64GB (16x4GB) DDR2-667 memory, 2x146 GB 10000 rpm SAS drive, DVD-ROM, 4 1133W Power Supply Units, Service Processor, 4x10/100/1000 Ethernet ports, 4 USB 2.0 ports, 2 PCI-X slots, 4 x8-lane PCIe slot, 2 x4-lane PCIe slot, and sliderail kit. No power cord, must order Geo-specific power cord option.RoHS-5. Standard Configuration.	8 921 800 Ft
SG-XPCIE8SAS-E-Z	Sun StorageTek (TM) 8-port external SAS PCI-Express Host Bus Adapter. RoHS 6. X-option	41 900 Ft
SGXPCIESAS-R-EXT-Z	Sun StorageTek (TM) 8-port external SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. X-Option.	90 300 Ft
X8098A	X-OPTION 8 GB Memory kit DDR2-667 Registered ECC DIMMs (2x4GB) for Sun Fire X4600 M2 x64 servers. RoHS-6.	88 700 Ft
X8356A	X-OPTION 16GB Memory kit DDR2-667 Registered ECC DIMMs (2x8 GB) for Sun Fire X4600 M2 x64 servers. RoHS-6.	547 800 Ft
X8123A-C-Z	4 GB Memory kit DDR2-667 Registered ECC single rank DIMMs (2x2 GB) for Sun Fire X4600 M2 x64 servers. RoHS-6. X-Option.	48 600 Ft
XRA-SS2CD-73G15K	73GB 15K RPM 2.5" SAS hard disk drive with Nemo bracket. RoHS-6. X-option.	48 900 Ft
XRB-SS2CD-146G10K	146GB 10K RPM 2.5" SAS hard disk drive with Nemo bracket. RoHS-6 Compliant. (x-option)	36 300 Ft
Sun Fire X4440		
B16-ZT4-DC-16C-RD6	Sun Fire X4440 x64 Server: 4x Enhanced AMD Opteron Model 8380 (2.5GHz/512KB) quad core processor, 8x 2GB DDR2-667 single rank memory, 4x146GB HDD, HBA RAID Card, DVD1RW, 2x PSU, Service processor, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 1x 16-lane PCIe slot, 4x 8-lane PCIe slots, 1x 4-lane PCIe slot, no Power Cord, order Geo-specific X-option. Standard Configuration. RoHS-5.	2 530 400 Ft

Part#	Description	Price
B16-ZW4-DC-16C-RD6	Sun Fire X4440 x64 Server: 4x AMD Enhanced Opteron Model 8384 (2.7GHz/512KB) quad core processor, 8x 2GB DDR2-667 single rank memory, 4x 146GB HDD, HBA RAID Card, DVD1RW, 2x PSU, Service processor, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 1x 16-lane PCIe slot, 4x 8-lane PCIe slots, 1x 4-lane PCIe slot, no Power Cord, order Geo-specific X-option. Solaris 10 Pre-Install. Standard Configuration. RoHS-5.	3 130 400 Ft
X6326A	Slide rail kit for Sun Fire X4140/X4170/X4270/X4440/X4150/X4450 server. Only fits in Sun Rack 938, Sun Rack 1038, Sun Rack 1042, or racks that have front to rear rail spacing between 610mm and 915mm (about 24" to about 36"). RoHS-6. X-option.	14 500 Ft
X8257A	AMD Opteron Model 8380 (2.5GHz/512KB) quad core processor for Sun Fire X4440 x64 servers. RoHS-5. X-Option.	326 100 Ft
X8256A	AMD Opteron Model 8376 HE (2.3GHz/512KB) quad core processor for Sun Fire X4440 x64 servers. RoHS-5. X-Option.	313 000 Ft
X8258A	AMD Opteron Model 8384 (2.7GHz/512KB) quad core processor for Sun Fire X4440 x64 servers. RoHS-5. X-Option.	482 600 Ft
X8260A	Mezzanine Card with 2x AMD Opteron Model 8376 HE (2.3GHz/512KB) quad core processors for Sun Fire X4440 x64 servers. Use only with matching Opteron Models. RoHS-5. X-Option.	626 100 Ft
X8261A	Mezzanine Card with 2x AMD Opteron Model 8380 (2.5GHz/512KB) quad core processors for Sun Fire X4440 x64 servers. Use only with matching Opteron Models. RoHS-5. X-Option.	652 200 Ft
X8262A	Mezzanine Card with 2x AMD Opteron Model 8384 (2.7GHz/512KB) quad core processors for Sun Fire X4440 x64 servers. Use only with matching Opteron Models. RoHS-5. X-Option.	952 200 Ft
XRB-SS2CD-146G10K	146GB 10K RPM 2.5" SAS hard disk drive with Nemo bracket. RoHS-6 Compliant. (x-option)	36 300 Ft
XRA-ST2CF-32G2SSD	2.5? 32GB SATA SSD (Type: SLC) with Marlin bracket, X-option RoHS-6	121 900 Ft
XRA-SS2CF-73G15K	73GB 15K RPM 2.5? SAS disk drive with Marlin bracket. RoHS-6. X-Option.	48 900 Ft
XRA-SS2CF-300G10K	300GB 10K RPM 2.5? SAS hard disk drive with Marlin bracket. (x-option) RoHS-6	65 700 Ft
X4287A	16 GB Memory kit DDR2-667 Registered ECC DIMMs (2x 8GB) for Sun Fire X4140/X4240/X4440 x64 servers. RoHS-5. X-Option.	547 800 Ft
SG-PCIE8SAS-I-Z	Sun StorageTek (TM) 8-Port internal SAS PCI-Express LSI 3081E Host Bus Adapter with RAID 0, 1, 1E support. RoHS-6. XATO.	57 400 Ft
SGXPCIESAS-R-INT-Z	Sun StorageTek (TM) 8-port internal SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. X-Option.	74 400 Ft
SG-XPCIE8SAS-E-Z	Sun StorageTek (TM) 8-port external SAS PCI-Express Host Bus Adapter. RoHS 6. X-option	41 900 Ft
X6323A	DVD+/-RW drive for Sun Fire X4150/X4250/X4450/X4140/X4240/X4440 server. RoHS-5. X-Option.	27 800 Ft

Part#	Description	Price
X6321A-C	X-Option 4 GB Memory kit DDR2-667 Registered ECC single rank DIMMs (2x 2GB) for Sun Fire X4140/X4240/X4440 x64 servers. RoHS-5.	48 600 Ft
X6328A	Redundant hot-swappable AC 1050W power supply unit for Sun Fire X4240/X4440/X4450 x64 servers. X-Option. RoHS-5.	33 600 Ft
X6322A	8 GB Memory kit DDR2-667 Registered ECC DIMMs (2x 4GB) for Sun Fire X4140/X4240/X4440 x64 servers. RoHS-5. X-Option.	88 700 Ft
Sun Fire X4240		
B14-AT2-DC-8C-RD6	Sun Fire X4240 x64 Server: 2x AMD Opteron Model 2380 (2.5GHz/512KB) quad core processor, 4x 2GB DDR2-667 single rank memory, 4x 146GB HDD, HBA RAID Card, DVD-RW, 2x PSU, HT Bridge Card, Service processor, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 1x 16-lane PCIe slot, 4x 8-lane PCIe slots, 1x 4-lane PCIe slot, no Power Cord, order Geo-specific X-option. Solaris 10 Pre-Install. Standard Configuration. RoHS-5.	1 173 900 Ft
B14-AW2-DC-8C-RD6	Sun Fire X4240 x64 Server: 2x AMD Opteron Model 2384 (2.7GHz/512KB) quad core processor, 4x 2GB DDR2-667 single rank memory, 4x 146GB HDD, HBA RAID Card, DVD-RW, 2x PSU, HT Bridge Card, Service processor, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 1x 16-lane PCIe slot, 4x 8-lane PCIe slots, 1x 4-lane PCIe slot, no Power Cord, order Geo-specific X-option. Solaris 10 Pre-Install. Standard Configuration. RoHS-5.	1 278 300 Ft
XRB-SS2CD-146G10K	146GB 10K RPM 2.5" SAS hard disk drive with Nemo bracket. RoHS-6 Compliant. (x-option)	36 300 Ft
XRA-ST2CF-32G2SSD	2.5? 32GB SATA SSD (Type: SLC) with Marlin bracket, X-option RoHS-6	121 900 Ft
XRA-SS2CF-73G15K	73GB 15K RPM 2.5? SAS disk drive with Marlin bracket. RoHS-6. X-Option.	48 900 Ft
XRA-SS2CF-300G10K	300GB 10K RPM 2.5? SAS hard disk drive with Marlin bracket. (x-option) RoHS-6	65 700 Ft
SG-PCIE8SAS-I-Z	Sun StorageTek (TM) 8-Port internal SAS PCI-Express LSI 3081E Host Bus Adapter with RAID 0, 1, 1E support. RoHS-6. XATO.	57 400 Ft
SGXPCIESAS-R-INT-Z	Sun StorageTek (TM) 8-port internal SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. X-Option.	74 400 Ft
X7280A-2	Sun PCI-E Low profile Dual GigE UTP, low profile bracket on board, standard bracket included. RoHS-6 compliant	62 600 Ft
X6328A	Redundant hot-swappable AC 1050W power supply unit for Sun Fire X4240/X4440/X4450 x64 servers. X-Option. RoHS-5.	33 600 Ft
X6321A-C	X-Option 4 GB Memory kit DDR2-667 Registered ECC single rank DIMMs (2x 2GB) for Sun Fire X4140/X4240/X4440 x64 servers. RoHS-5.	48 600 Ft
X6323A	DVD+/-RW drive for Sun Fire X4150/X4250/X4450/X4140/X4240/X4440 server. RoHS-5. X-Option.	27 800 Ft
Sun Fire X2270		

Part#	Description	Price
SSH-X2270-B	Sun Fire X2270 base configuration. no CPU, no HDD, no RAM	176 100 Ft
SSH-X2270-S	Sun Fire X2270, 1x Intel Xeon E5504 Processor (2.0Ghz, 4MB L3 Cache per Processor), 2GB (1x 2GB, DDR3-1066) memory, 48GB max memory, No HDD, No DVD, 1x PSU, ILOM, 2x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 1x PCIe 2.0 I/O slot.	244 900 Ft
SSH-X2270-M	Sun Fire X2270, 2x Intel Xeon E5504 Processor (2.0Ghz, 4MB L3 Cache per Processor), 12GB (6x 2GB, DDR3-1066) memory, 48GB max memory, No HDD, No DVD, 1x PSU, ILOM, 2x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 1x PCIe 2.0 I/O slot.	347 100 Ft
SSH-X2270-L	Sun Fire X2270, 2x Intel Xeon E5540 Processor (2.53Ghz, 4MB L3 Cache per Processor), 12GB (6x 2GB, DDR3-1333) memory, 48GB max memory, No HDD, No DVD, 1x PSU, ILOM, 2x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 1x PCIe 2.0 I/O slot.	629 300 Ft
SSH-X2270-XL	Sun Fire X2270, 2x Intel Xeon E5540 Processor (2.53Ghz, 4MB L3 Cache per Processor), 48GB (12x 4GB, DDR3-1333) memory, 48GB max memory, No HDD, No DVD, 1x PSU, ILOM, 2x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 1x PCIe 2.0 I/O slot.	832 400 Ft
SSH-X2270-SH	Sun Fire X2270, 1x Intel Xeon E5504 Processor (2.0Ghz, 4MB L3 Cache per Processor), 6GB (3x 2GB, DDR3-1066) memory, 48GB max memory, 4x 500GB 7.2 RPM SATA, No DVD, 1x PSU, ILOM, 2x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 1x PCIe 2.0 I/O slot. Üzemkész konfiguráció, mely tartalmazza a merevlemezeket	402 600 Ft
SSH-X2270-MH	Sun Fire X2270, 2x Intel Xeon E5504 Processor (2.0Ghz, 4MB L3 Cache per Processor), 6GB (3x 2GB, DDR3-1066) memory, 48GB max memory, 4x 500GB 7.2 RPM SATA, No DVD, 1x PSU, ILOM, 2x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 1x PCIe 2.0 I/O slot. Üzemkész konfiguráció, mely tartalmazza a merevlemezeket	483 100 Ft
SSH-X2270-LH	Sun Fire X2270, 2x Intel Xeon E5540 Processor (2.53Ghz, 4MB L3 Cache per Processor), 12GB (6x 2GB, DDR3-1333) memory, 48GB max memory, 4x 500GB 7.2 RPM SATA, No DVD, 1x PSU, ILOM, 2x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 1x PCIe 2.0 I/O slot Üzemkész konfiguráció, mely tartalmazza a merevlemezeket.	763 100 Ft
SSH-X2270-XLH	Sun Fire X2270, 2x Intel Xeon E5540 Processor (2.53Ghz, 4MB L3 Cache per Processor), 48GB (12x 4GB, DDR3-1333) memory, 48GB max memory, 4x 500GB 7.2 RPM SATA, No DVD, 1x PSU, ILOM, 2x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 1x PCIe 2.0 I/O slot Üzemkész konfiguráció, mely tartalmazza a merevlemezeket.	966 300 Ft
RA-ST1CR-500G7K	500GB 7.2K RPM, 3.5 inch SATA HDD with coral bracket, ATO	33 500 Ft
8348A	X2100/X4100/X4200: Slide rail	12 100 Ft
RA-ST1CR-1T7K	1TB 7.2K RPM, 3.5 inch SATA HDD with coral bracket. RoHS-6. X-option.	65 700 Ft
RA-ST1CR-32G2SSD	32GB 3.5 inch SATA SSD with coral bracket. Type:SLC, x-option, ROHS 6	131 300 Ft
8340A	Sun Integrated Lights Out Management (ILOM) Service Processor Module, AST2100 on a mezzanine card option for Sun Fire X2270 Server	12 200 Ft

Part#	Description	Price
X7280A-2	Sun PCI-E Low profile Dual GigE UTP, low profile bracket on board, standard bracket included. RoHS-6 compliant	62 600 Ft
8330A	2.26 GHz Intel Xeon L5520 with 8 MB Cache, 5.86 GT/s QPI, DDR3-1066, Turbo On, HT On, 60W, for Sun Fire X2270 Server, RoHS-5 Compliant	125 900 Ft
8331A	2.00 GHz Intel Xeon E5504 with 4 MB Cache, 4.8 GT/s QPI, DDR3-800, Turbo Off, HT Off, 80W, for Sun Fire X2270 Server, RoHS-5 Compliant	44 800 Ft
8332A	2.53 GHz Intel Xeon E5540 with 8 MB Cache, 5.86 GT/s QPI, DDR3-1066, Turbo On, HT On, 80W, for Sun Fire X2270 Server, RoHS-5 Compliant	182 600 Ft
8333A	2.66 GHz Intel Xeon X5550 with 8 MB Cache, 6.4 GT/s QPI, DDR3-1333, Turbo On, HT On, 95W, for Sun Fire X2270 Server, RoHS-5 Compliant	239 300 Ft
8334A	2.93 GHz Intel Xeon X5570 with 8 MB Cache, 6.4 GT/s QPI, DDR3-1333, Turbo On, HT On, 95W, for Sun Fire X2270 Server, RoHS-5 Compliant	352 700 Ft
8335A	2 GB (1 x 2 GB DIMMs) DDR3-1066 Registered ECC Memory, for Sun Fire X2270 Server, RoHS-5 Compliant	11 900 Ft
8337A	2 GB (1 x 2 GB DIMMs) DDR3-1333 Registered ECC Memory, for Sun Fire X2270 Server, RoHS-5 Compliant	12 600 Ft
8338A	4 GB (1 x 4 GB DIMMs) DDR3-1333 Registered ECC Memory, for Sun Fire X2270 Server, RoHS-5 Compliant	23 300 Ft
SG-XPCIE8SAS-E-Z	Sun StorageTek (TM) 8-port external SAS PCI-Express Host Bus Adapter. RoHS 6. X-option	41 900 Ft
Sun Fire X4170		
SSH-X4170-B	Sun Fire X4170 base configuration, no CPU, no HDD, no RAM	345 100 Ft
SSH-X4170-S	1 Intel Xeon E5520 Quad-Core processor (8MB cache, 2.26 GHz, 1066 MHz FSB) Nehalem-EP, 6GB (3x 2GB, 1066MHz DDR3), no HDD, SAS controller, no DVD, 1x PSU, ILOM, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 3x 8-lane PCI-Express slots, no power cord, order Geo-specific x-option. RoHS-5.	518 800 Ft
SSH-X4170-M	2 Intel Xeon E5520 Quad-Core processor (8MB cache, 2.26 GHz, 1066 MHz FSB) Nehalem-EP, 12GB (6 x 2GB, 1066MHz DDR3), no HDD, SAS RAID HBA, no DVD, 1 x PSU, ILOM, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 3x 8-lane PCI-Express slots, no power cord, order Geo-specific x-option. RoHS-5.	797 300 Ft
SSH-X4170-L	2 Intel Xeon E5540 Quad-Core processor (8MB cache, 2.53 GHz, 1066 MHz FSB) Nehalem-EP, 12GB (6 x 2GB, 1066MHz DDR3), no HDD, SAS BBWC RAID HBA, no DVD, 2 x PSU, ILOM, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 3x 8-lane PCI-Express slots, no power cord, order Geo-specific x-option. RoHS-5.	884 600 Ft

Part#	Description	Price
SSH-X4170-XL	2 Intel Xeon E5570 Quad-Core processor (8MB cache, 2.93 GHz) Nehalem-EP, 24GB (6x 4GB, 1333MHz DDR3), no HDD, SAS controller, no DVD, 1x PSU, ILOM, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 3x 8-lane PCI-Express slots, no power cord, order Geo-specific x-option. RoHS-5.	947 800 Ft
SSH-X4170-SH	1 Intel Xeon E5520 Quad-Core processor (8MB cache, 2.26 GHz, 1066 MHz FSB) Nehalem-EP, 6GB (3x 2GB, 1066MHz DDR3), 2x 146GB 10K RPM 2.5 SAS HDD, SAS controller, no DVD, 1x PSU, ILOM, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 3x 8-lane PCI-Express slots, no power cord, order Geo-specific x-option. RoHS-5. Üzemkész konfiguráció, mely tartalmazza a merevlemezeket	591 400 Ft
SSH-X4170-MH	2 Intel Xeon E5520 Quad-Core processor (8MB cache, 2.26 GHz, 1066 MHz FSB) Nehalem-EP, 12GB (6 x 2GB, 1066MHz DDR3), 4x 146GB 10K RPM 2.5 SAS HDD, SAS RAID HBA, no DVD, 1 x PSU, ILOM, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 3x 8-lane PCI-Express slots, no power cord, order Geo-specific x-option. RoHS-5. Üzemkész konfiguráció, mely tartalmazza a merevlemezeket	797 300 Ft
SSH-X4170-LH	2 Intel Xeon E5540 Quad-Core processor (8MB cache, 2.53 GHz, 1066 MHz FSB) Nehalem-EP, 12GB (6 x 2GB, 1066MHz DDR3), 4x 146GB 10K RPM 2.5 SAS HDD, SAS BBWC RAID HBA, no DVD, 2 x PSU, ILOM, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 3x 8-lane PCI-Express slots, no power cord, order Geo-specific x-option. RoHS-5. Üzemkész konfiguráció, mely tartalmazza a merevlemezeket	1 182 200 Ft
SSH-X4170-XLH	2 Intel Xeon E5570 Quad-Core processor (8MB cache, 2.93 GHz) Nehalem-EP, 24GB (6x 4GB, 1333MHz DDR3), 8x 146GB 10K RPM 2.5 SAS HDD, SAS controller, no DVD, 1x PSU, ILOM, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 3x 8-lane PCI-Express slots, no power cord, order Geo-specific x-option. RoHS-5. Üzemkész konfiguráció, mely tartalmazza a merevlemezeket	1 888 100 Ft
6326A	Slide rail kit for Sun Fire X4140/X4170/X4270/X4440/X4150/X4450 server. Only fits in Sun Rack 938, Sun Rack 1038, Sun Rack 1042, or racks that have front to rear rail spacing between 610mm and 915mm (about 24" to about 36"). RoHS-6. X-option.	14 500 Ft
XRB-SS2CD-146G10K	146GB 10K RPM 2.5" SAS hard disk drive with Nemo bracket. RoHS-6 Compliant. (x-option)	36 300 Ft
XRA-ST2CF-32G2SSD	2.5? 32GB SATA SSD (Type: SLC) with Marlin bracket, X-option RoHS-6	121 900 Ft
XRA-SS2CF-73G15K	73GB 15K RPM 2.5? SAS disk drive with Marlin bracket. RoHS-6. X-Option.	48 900 Ft
XRA-SS2CF-300G10K	300GB 10K RPM 2.5? SAS hard disk drive with Marlin bracket. (x-option) RoHS-6	65 700 Ft
X8325A	DVD+/-RW SATA-based drive for Sun Fire X4170/X4270 x64 servers. RoHS-5. X-Option.	27 800 Ft
X5872A	Redundant hot-swappable AC 760W power supply unit for Sun Fire X4170 x64 servers. X-Option. RoHS-6.	23 700 Ft

Part#	Description	Price
X4680A	16 GB Compact Flash Card; Used for flash based booting and OS image pre-loads. RoHS 5. X-Option.	43 600 Ft
SG-XPCIE8SAS-E-Z	Sun StorageTek (TM) 8-port external SAS PCI-Express Host Bus Adapter. RoHS 6. X-option	41 900 Ft
SGXPCIESAS-R-INT-Z	Sun StorageTek (TM) 8-port internal SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. X-Option.	74 400 Ft
SG-PCIE8SAS-I-Z	Sun StorageTek (TM) 8-Port internal SAS PCI-Express LSI 3081E Host Bus Adapter with RAID 0, 1, 1E support. RoHS-6. XATO.	57 400 Ft
5861A	1 Intel Xeon Model Number X5570 Quad-Core (2.93GHz/95W) Processor without Heatsink for Sun Fire X4170 & Sun Fire X4270 & Sun Fire X4275 Servers. RoHS-6. For Factory Integration Only.	348 800 Ft
5862A	1 Intel Xeon Model Number X5560 Quad-Core (2.8GHz/95W) Processor without Heatsink for Sun Fire X4170 & Sun Fire X4270 & Sun Fire X4275 Servers. For Factory Integration Only.	292 100 Ft
5863A	1 Intel Xeon E5540, 4C, 2.53 GHz, 80W, 8MB Cache, Intel Turbo Boost Technology, Intel HT Technology Processor without Heatsink for Sun Fire X4170, Sun Fire X4270 & Sun Fire X4275 Servers. RoHS-6 Compliant. For Factory Integration Only.	178 600 Ft
5864A	1 Intel Xeon L5520, 4C, 2.26 GHz, 60W, 8MB Cache, Intel Turbo Boost Technology, Intel HT Technology Processor without Heatsink for Sun Fire X4170, Sun Fire X4270 & Sun Fire X4275 Servers. RoHS-6 Compliant. For Factory Integration Only.	121 900 Ft
5865A	1 Intel Xeon Model Number E5520 Quad-Core (2.26GHz/80W) Processor without Heatsink for Sun Fire X4170 & Sun Fire X4270 & Sun Fire X4275 Servers. RoHS-6. For Factory Integration Only.	80 500 Ft
5870A	4 GB Memory kit DDR3-1333 Registered ECC DIMMs (1 x 4 GB) for Sun Fire X4170, X4270 & X4275 x64 servers. RoHS-6. For Factory Integration Only.	23 300 Ft
5867A	4 GB Memory kit DDR3-1066 Registered ECC DIMMs (1 x 4 GB) for Sun Fire X4170, X4270 & X4275 x64 servers. RoHS-6. For Factory Integration Only.	22 900 Ft
5866A	2 GB Memory kit DDR3-1066 Registered ECC DIMMs (1 x 2 GB) for Sun Fire X4170, X4270 & X4275 x64 servers. RoHS-6. For Factory Integration Only.	11 900 Ft
Sun Fire X4270		
SSH-X4270-B	Sun Fire X4270 base configuration, no CPU, no HDD, no RAM	480 900 Ft
SSH-X4270-S	1 Intel Xeon E5520 Quad-Core processor (8MB cache, 2.26 GHz, 1066 MHz FSB) Nehalem-EP, 6GB (3 x 2GB, 1066MHz DDR3), no HDD, SAS controller, no DVD, 1x PSU, ILOM, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports, 3x 8-lane PCI-Express slots, no power cord, order Geo-specific x-option. RoHS-5.	677 600 Ft

Part#	Description	Price
6326A	Slide rail kit for Sun Fire X4140/X4170/X4270/X4440/X4150/X4450 server. Only fits in Sun Rack 938, Sun Rack 1038, Sun Rack 1042, or racks that have front to rear rail spacing between 610mm and 915mm (about 24" to about 36"). RoHS-6. X-option.	14 500 Ft
6328A	Redundant hot-swappable AC 1050W power supply unit for Sun Fire X4240/X4440/X4450 x64 servers. X-Option. RoHS-5.	33 600 Ft
5861A	1 Intel Xeon Model Number X5570 Quad-Core (2.93GHz/95W) Processor without Heatsink for Sun Fire X4170 & Sun Fire X4270 & Sun Fire X4275 Servers. RoHS-6. For Factory Integration Only.	348 800 Ft
5862A	1 Intel Xeon Model Number X5560 Quad-Core (2.8GHz/95W) Processor without Heatsink for Sun Fire X4170 & Sun Fire X4270 & Sun Fire X4275 Servers. For Factory Integration Only.	292 100 Ft
5863A	1 Intel Xeon E5540, 4C, 2.53 GHz, 80W, 8MB Cache, Intel Turbo Boost Technology, Intel HT Technology Processor without Heatsink for Sun Fire X4170, Sun Fire X4270 & Sun Fire X4275 Servers. RoHS-6 Compliant. For Factory Integration Only.	178 600 Ft
SG-XPCIE8SAS-E-Z	Sun StorageTek (TM) 8-port external SAS PCI-Express Host Bus Adapter. RoHS 6. X-option	41 900 Ft
SG-PCIE8SAS-I-Z	Sun StorageTek (TM) 8-Port internal SAS PCI-Express LSI 3081E Host Bus Adapter with RAID 0, 1, 1E support. RoHS-6. XATO.	57 400 Ft
SGXPCIESAS-R-INT-Z	Sun StorageTek (TM) 8-port internal SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. X-Option.	74 400 Ft
5865A	1 Intel Xeon Model Number E5520 Quad-Core (2.26GHz/80W) Processor without Heatsink for Sun Fire X4170 & Sun Fire X4270 & Sun Fire X4275 Servers. RoHS-6. For Factory Integration Only.	80 500 Ft
XRB-SS2CD-146G10K	146GB 10K RPM 2.5" SAS hard disk drive with Nemo bracket. RoHS-6 Compliant. (x-option)	36 300 Ft
XRA-ST2CF-32G2SSD	2.5? 32GB SATA SSD (Type: SLC) with Marlin bracket, X-option RoHS-6	121 900 Ft
XRA-SS2CF-300G10K	300GB 10K RPM 2.5? SAS hard disk drive with Marlin bracket. (x-option) RoHS-6	65 700 Ft
5870A	4 GB Memory kit DDR3-1333 Registered ECC DIMMs (1 x 4 GB) for Sun Fire X4170, X4270 & X4275 x64 servers. RoHS-6. For Factory Integration Only.	23 300 Ft
5867A	4 GB Memory kit DDR3-1066 Registered ECC DIMMs (1 x 4 GB) for Sun Fire X4170, X4270 & X4275 x64 servers. RoHS-6. For Factory Integration Only.	22 900 Ft
5866A	2 GB Memory kit DDR3-1066 Registered ECC DIMMs (1 x 2 GB) for Sun Fire X4170, X4270 & X4275 x64 servers. RoHS-6. For Factory Integration Only.	11 900 Ft
X8325A	DVD+/-RW SATA-based drive for Sun Fire X4170/X4270 x64 servers. RoHS-5. X-Option.	27 800 Ft
Sun Fire X4275		
SSH-X4275-B	Sun Fire X4275 base configuration, no CPU, no HDD, no RAM	480 900 Ft

Part#	Description	Price
X5889A	Tool-less Slide Rail Kit for Sun Fire X4275 x64 servers. X-Option. RoHS-6.	12 700 Ft
5870A	4 GB Memory kit DDR3-1333 Registered ECC DIMMs (1 x 4 GB) for Sun Fire X4170, X4270 & X4275 x64 servers. RoHS-6. For Factory Integration Only.	23 300 Ft
5867A	4 GB Memory kit DDR3-1066 Registered ECC DIMMs (1 x 4 GB) for Sun Fire X4170, X4270 & X4275 x64 servers. RoHS-6. For Factory Integration Only.	22 900 Ft
5866A	2 GB Memory kit DDR3-1066 Registered ECC DIMMs (1 x 2 GB) for Sun Fire X4170, X4270 & X4275 x64 servers. RoHS-6. For Factory Integration Only.	11 900 Ft
X4680A	16 GB Compact Flash Card; Used for flash based booting and OS image pre-loads. RoHS 5. X-Option.	43 600 Ft
SG-PCIE8SAS-I-Z	Sun StorageTek (TM) 8-Port internal SAS PCI-Express LSI 3081E Host Bus Adapter with RAID 0, 1, 1E support. RoHS-6. XATO.	57 400 Ft
SGXPCIESAS-R-INT-Z	Sun StorageTek (TM) 8-port internal SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. X-Option.	74 400 Ft
XRA-ST1CR-32G2SSD	32GB 3.5 inch SATA SSD with coral bracket. Type:SLC, x-option, ROHS 6	131 300 Ft
XRA-SS1CR-300G15K	300GB 15K RPM, 3.5 inch SAS HDD with coral bracket, x-option, ROHS 6	77 900 Ft
XRA-SS1CR-450G15K	450GB 15K RPM, 3.5 inch SAS HDD with coral bracket, x-option, ROHS 6	96 700 Ft
XRA-ST1CR-1T7K	1TB 7.2K RPM, 3.5 inch SATA HDD with coral bracket. RoHS-6. X-option.	65 700 Ft
X5861A-2U	1 Intel. Xeon. X5570, 4C, 2.93GHz, 95W, 8MB Cache, Intel. Turbo Boost Technology, Intel. HT Technology Processor with Heatsink for Sun Fire X4270 & Sun Fire X4275 Servers. RoHS-6. X-Option Only.	359 400 Ft
X5862A-2U	1 Intel. Xeon. X5560, 4C, 2.8GHz, 95W, 8MB Cache, Intel. Turbo Boost Technology, Intel. HT Technology Processor with Heatsink for Sun Fire X4270 & Sun Fire X4275 Servers. X-Option Only.	305 300 Ft
X5863A-2U	1 Intel. Xeon. E5540, 4C, 2.53GHz, 80W, 8MB Cache, Intel. Turbo Boost Technology, Intel. HT Technology Processor with Heatsink for Sun Fire X4270 & Sun Fire X4275 Servers. RoHS-6. X-Option Only.	197 100 Ft
X5864A-2U	1 Intel. Xeon. L5520, 4C, 2.26GHz, 60W, 8MB Cache, Intel. Turbo Boost Technology, Intel. HT Technology Processor with Heatsink for Sun Fire X4270 & Sun Fire X4275 Servers. RoHS-6. For X-Option Only.	143 000 Ft
X5865A-2U	1 Intel. Xeon. E5520, 4C, 2.26GHz, 80W, 8MB Cache, Intel. Turbo Boost Technology, Intel. HT Technology Processor with Heatsink for Sun Fire X4270 & Sun Fire X4275 Servers. RoHS-6. For X-Option Only.	103 600 Ft
Ultra 24		

Part#	Description	Price
B21-TUZ1-AU-2GDU	Sun Ultra 24 Workstation 1 Intel* Core2 Quad Extreme Q9650 (Yorkfield) 3.0Ghz, 1333Mhz FSB, Two 1GB DIMMs (Unbuffered, ECC, DDR2-667), One 250GB 7,200 rpm SATA 3.0Gbps HDD, pre-installed with Solaris 10, Update 4, NetBeans 5.5.1 Sun Studio 12, One NVIDIA FX370 Graphics Accelerator, One DVD-Dual (Write/Read DVDs/CDs. DVDs in + formats, on both layers). ROHS COMPLIANT.	313 000 Ft
B21-TVZ1-AC-1GDU	Sun Ultra 24 Workstation, 1 Intel* Core2 Duo Extreme E8600 (Wolfdate) 3.3Ghz, 1333Mhz FSB One 1GB DIMMs (Unbuffered, ECC, DDR2-667), One 250GB 7,200 rpm SATA 3.0Gbps HDD, pre-installed with Solaris 10, Update 4, NetBeans 5.5.1 Sun Studio 12 One NVIDIA Quadro FX 1700 Graphics Accelerator, One DVD-Dual (Write/Read DVDs/CDs. DVDs in + formats, on both layers). ROHS COMPLIANT.	313 000 Ft
X7237A	22-inch Widescreen LCD Monitor. 1680x1050 resolution, 300 cd/m2 luminance level (typical), 8 ms response time (gray-to-gray, typical), 1000:1 contrast ratio (typical), DVI-D (Digital) and HD15 (Analog) inputs, 2 video cables included (HD15/HD15, 1.8 meters, and DVI-D/DVI-D, 3 meters). Sun logo and color. RoHS-6 compliant. Must order country-specific power cord. X-option.	57 400 Ft
X7236A	24.1-inch TFT LCD Color Monitor (27 inch CRT equivalent), PVA wide viewing angle, 1920x1200@60 Hz, digital input: DVI-D, analog input: HD15, 4-port USB 2.0 hub, fully HDTV compatible, HDCP, full set of cables for all interfaces included, Digital OSD controls, VESA DPMS, TCO'03, WW agency compliances, Sun ID enclosure, Sun logo and color, RoHS compliant	151 300 Ft
X4100A-Z	X-Option NVIDIA Quadro FX370 Entry 3D graphics accelerator. RoHS 6 Compliant.	27 800 Ft
X4129A-Z	X-Option NVIDIA Quadro FX 1700 mid-range 3D graphics accelerator. RoHS-6.	125 200 Ft
X4130A-Z	X-Option, NVIDIA Quadro FX 570 entry 3D graphics accelerator. RoHS-6.	47 000 Ft
X4083A-Z	RoHS-6 compliant. X-Option NVIDIA Quadro FX 4600 high-end 3D graphics accelerator. SLI Ready. RoHS-6.	352 200 Ft
X4084A-Z	RoHS-6 compliant. X-Option NVIDIA Quadro FX 5600 ultra high-end 3D graphics accelerator. SLI Ready. RoHS-6.	573 900 Ft
X4128A-Z	X-Option NVIDIA Quadro FX 3700 high-end 3D graphics accelerator. RoHS-6.	185 200 Ft
Ultra 27		
U27-B	Sun Ultra 27 base configuration. No CPU, no HDD, no DVD.	148 700 Ft
U27-S	Sun Ultra 27 Workstation 1 Intel Xeon 3520 2.66Ghz, Three 1GB DIMMs (1066MHz), One 500GB 7,200 rpm SATA 3.0Gbps HDD, pre-installed with Solaris 10, One NVIDIA FX380 Graphics Accelerator, One DVD-Dual (Write/Read DVDs/CDs. DVDs in + formats, on both layers). ROHS COMPLIANT.	367 500 Ft

Part#	Description	Price
U27-M	Sun Ultra 27 Workstation 1 Intel Xeon 3520 2.66Ghz, Three 2GB DIMMs (1066MHz), Two 500GB 7,200 rpm SATA 3.0Gbps HDD, pre-installed with Solaris 10, One NVIDIA FX380 Graphics Accelerator, One DVD-Dual (Write/Read DVDs/CDs. DVDs in + formats, on both layers). ROHS COMPLIANT.	444 100 Ft
U27-XL	Sun Ultra 27 Workstation 1 Intel Xeon 3540 2.93Ghz, Three 2GB DIMMs (1333MHz), Two 500GB 7,200 rpm SATA 3.0Gbps HDD, pre-installed with Solaris 10, One NVIDIA FX1800 Graphics Accelerator, One DVD-Dual (Write/Read DVDs/CDs. DVDs in + formats, on both layers). ROHS COMPLIANT.	635 800 Ft
U27-SRV	Sun Ultra 27 Workstation 1 Intel Xeon 3540 2.93Ghz, 6x 2GB DIMMs (1333MHz), 4x 300GB 15RPM SAS HDD, RAID controller, pre-installed with Solaris 10, One NVIDIA FX1800 Graphics Accelerator, One DVD-Dual (Write/Read DVDs/CDs. DVDs in + formats, on both layers), Dual Gigabit Ethernet PCI-E card, ROHS COMPLIANT.	917 900 Ft
3911A	Intel Xeon Processor 3570 (3.2 GHz, Quad Core, 6.4 GT/s Quick Path Interconnect, 1333MHz DDR3 memory controller, 8MB L3 cache, HyperThreading-enabled, Intel Turbo Boost-enabled, 130W TDP)	339 100 Ft
3912A	Intel Xeon Processor 3540 (2.93 GHz, Quad-Core, 4.8 GT/s QuickPath Interconnect, 1066MHz DDR3 memory controller, 8MB L3 cache, HyperThreading-enabled, Intel Turbo Boost-enabled, 130W TDP)	194 000 Ft
3913A	Intel Xeon Processor 3520 (2.66 GHz, Quad-Core, 4.8 GT/s QuickPath Interconnect, 1066MHz DDR3 memory controller, 8MB L3 cache, HyperThreading-enabled, Intel Turbo Boost-enabled, 130W TDP)	93 900 Ft
3918A	ATO NVIDIA Quadro FX 3800 Graphics Card. RoHS-5 Compliant	229 600 Ft
3919A	ATO NVIDIA Quadro FX 1800 Graphics Card. RoHS-5 Compliant	125 200 Ft
3921A	Nvidia Quadro FX 380 Graphics Accelerator Card, For XATO and Factory Integration, RoHS-5.	35 900 Ft
3923A	ATO NVIDIA Quadro FX 5800 Graphics Card. ROHS 5 Compliant.	926 100 Ft
8015A-Z	DVI-to-VGA Adapter. RoHS-6	2 900 Ft
3914A	ATO 1 x 2 GB DDR3-1333MHz Unbuffered DIMM for Sun Ultra 27 Workstation, RoHS-5 Compliant	27 800 Ft
3915A	ATO 1 x 2 GB DDR3-1066MHz unbuffered DIMM for Sun Ultra 27 Workstation, RoHS-5 Compliant	25 900 Ft
3916A	ATO 1 x 1 GB DDR3-1066MHz unbuffered DIMM for Sun Ultra 27 Workstation, RoHS-5 Compliant	11 500 Ft
SG-XPCIE4SAS3-Z	4 x1 4-Port SAS PCI-E HBA internal connection LSI3041E with B3 silicon X-Option. RoHS-6 compliant.	46 100 Ft
RB-ST1CE-500G7K	X-Option Internal 500GB 7,200 RPM 3.5-inch Serial ATA Hard Disk Drive with bracket. RoHS-6.	25 300 Ft

Part#	Description	Price
RB-ST1CE-1T7K	Internal 3.5-inch 1TB 7200 rpm Serial ATA Hard Disk Drive with bracket. X-option. RoHS-6.	38 600 Ft
RB-SS1CE-146G15KZ	RoHS-6. Internal 146GB 15K SAS HDD, 3.5" x 1" drive with bracket.	38 500 Ft
RB-SS1CE-300G15K	RoHS-6. Internal 300GB 15K SAS HDD, 3.5" x 1" drive with bracket.	61 600 Ft
X7280A-2	Sun PCI-E Low profile Dual GigE UTP, low profile bracket on board, standard bracket included. RoHS-6 compliant	62 600 Ft
4133A-Z	ATO Option DVD Dual for Sun Ultra 24 & Ultra 27 Workstation. 16X DVD+/-RW Drive supports read/write in dual +/- formats. Supports double-layer DVD to hold up to 8.5GB or single-layer DVD to hold up to 4.7GB. SATA. RoHS-6.	21 100 Ft
X7204A	17-inch TFT-LCD Monitor, TN technology, 500:1 contrast ratio, 300 cd/m2 luminance, 70 degree viewing angle, 1280x1024 @ 60 Hz, Analog RGB video through HD15 connector and HD15/HD15 cable, Digital TMDS video through DVI-D connector and DVI-D/DVI-D cable, with tilt adjustments, integral power supply, Energy Star and TCO'99 WW Agency compliances, Sun colors enclosure with Sun logos on front bezel, rear cabinet and base stand. RoHS Compliant.	40 500 Ft
X7205A	19-inch TFT LCD Color Monitor, 19-inch viewable area, 0.294mm pixel pitch, Brightness 300cd/m2 (typ), 500:1 contrast ratio (typ), Response time 5ms (typ), 1280x1024 @ 60Hz, 170 degree viewing angle, Internal power supply, Tilt, Analog(HD15) and Digital Input(DVI), 410mm(W) x 406mm(H) x 213.7mm(D), Weight: 3.9kg / 8.59lbs, Power Consumption 37 Watts max, HD15 to HD15 video cable and DVI-D to DVI-D video cable included, WW Agency comp, Energy Star, TCO '99, EU, China, RoHS.	46 100 Ft
X7237A	22-inch Widescreen LCD Monitor. 1680x1050 resolution, 300 cd/m2 luminance level (typical), 8 ms response time (gray-to-gray, typical), 1000:1 contrast ratio (typical), DVI-D (Digital) and HD15 (Analog) inputs, 2 video cables included (HD15/HD15, 1.8 meters, and DVI-D/DVI-D, 3 meters). Sun logo and color. RoHS-6 compliant. Must order country-specific power cord. X-option.	57 400 Ft
X7236A	24.1-inch TFT LCD Color Monitor (27 inch CRT equivalent), PVA wide viewing angle, 1920x1200@60 Hz, digital input: DVI-D, analog input: HD15, 4-port USB 2.0 hub, fully HDTV compatible, HDCP, full set of cables for all interfaces included, Digital OSD controls, VESA DPMS, TCO'03, WW agency compliances, Sun ID enclosure, Sun logo and color, RoHS compliant	151 300 Ft
X3868A	Type 7 European Universal Country Kit. RoHS-6 (Lead-Free) Compliant.	11 600 Ft
StorageTek 2530 SAS		
XTA2530R01A1L3750	Sun StorageTek(TM) 2530 SAS Array, Rack-Ready Controller Tray, 3750GB, 5 * 750GB 7.2Krpm SATA-II drives, 1 * 512MB cache SAS HW RAID controller, 2 * redundant AC power supplies, 2 * redundant cooling fans; Includes Sun StorageTek(TM) Common Array Manager software and 2 * storage domains using Sun StorageTek(TM) Storage Domains software; RoHS-5	1 487 000 Ft

Part#	Description	Price
XTA2530R01A1N5000	Sun StorageTek(TM) 2530 SAS Array, Rack-Ready Controller Tray, 5TB, 5 * 1TB 7.2Krpm SATA-II drives, 1 * 512MB cache SAS HW RAID controller, 2 * redundant AC power supplies, 2 * redundant cooling fans; Includes Sun StorageTek(TM) Common Array Manager software and 2 * storage domains using Sun StorageTek(TM) Storage Domains software; RoHS-5	1 852 200 Ft
XTA-2500-2URK-19U	Sun StorEdge(TM) 2500 2U universal rack, adjustable depth rail kit; RoHS-5	29 600 Ft
SG-XPCIE8SAS-E-Z	Sun StorageTek (TM) 8-port external SAS PCI-Express Host Bus Adapter. RoHS 6. X-option	41 900 Ft
SGXPCIESAS-R-EXT-Z	Sun StorageTek (TM) 8-port external SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. X-Option.	90 300 Ft
StorageTek 2510 iSCSI		
XTA2510R01A1A2500	Sun StorageTek(TM) 2510 iSCSI Array, Rack-Ready Controller Tray, 2500GB, 5 * 500GB 7.2Krpm SATA drives, 1 * 512MB cache iSCSI HW RAID controller, 2 * redundant AC power supplies, 2 * redundant cooling fans, Includes Sun StorageTek(TM) Common Array Manager software and 2 * storage domains using Sun StorageTek(TM) Storage Domains software; RoHS-5	1 304 400 Ft
XTA2510R01A1L3750	Sun StorageTek(TM) 2510 iSCSI Array, Rack-Ready Controller Tray, 3750GB, 5 * 750GB 7.2Krpm SATA drives, 1 * 512MB cache iSCSI HW RAID controller, 2 * redundant AC power supplies, 2 * redundant cooling fans, Includes Sun StorageTek(TM) Common Array Manager software and 2 * storage domains using Sun StorageTek(TM) Storage Domains software; RoHS-5	1 460 900 Ft
XTA2510R01A2N12000	Sun StorageTek(TM) 2510 iSCSI Array, Rack-Ready Controller Tray, 12TB, 12 * 1TB 7.2Krpm SATA-II drives, 2 * 512MB cache iSCSI HW RAID controllers, 2 * redundant AC power supplies, 2 * redundant cooling fans; Includes Sun StorageTek(TM) Common Array Manager software and 2 * storage domains using Sun StorageTek(TM) Storage Domains software; RoHS-5	3 547 800 Ft
XTA-2500-2URK-19U	Sun StorEdge(TM) 2500 2U universal rack, adjustable depth rail kit; RoHS-5	29 600 Ft
StorageTek 2540 FC		
XTA2540R01A1N5000	Sun StorageTek(TM) 2540 FC Array, Rack-Ready Controller Tray, 5TB, 5* 1TB 7.2Krpm SATA-II drives, 1 * 512MB cache FC HW RAID controller, 2 * redundant AC power supplies, 2 * redundant cooling fans, and 2 * shortwave SFPs; Includes Sun StorageTek(TM) Common Array Manager software and 2 * storage domains using Sun StorageTek(TM) Storage Domains software; RoHS-5	1 878 300 Ft

Part#	Description	Price
XTA2540R01A1F3600	Sun StorageTek(TM) 2540 FC Array, Rack-Ready Controller Tray, 3600GB, 12 * 300GB 15Krpm SAS drives, 1 * 512MB cache FC HW RAID controller, 2 * redundant AC power supplies, 2 * redundant cooling fans, 2 * shortwave SFPs; Includes Sun StorageTek(TM) Common Array Manager software and 2 * storage domains using Sun StorageTek(TM) Storage Domains software; RoHS-5	2 791 300 Ft
XTA2540R01A2F3600	Sun StorageTek(TM) 2540 FC Array, Rack-Ready Controller Tray, 3600GB, 12 * 300GB 15Krpm SAS drives, 2 * 512MB cache FC HW RAID controllers, 2 * redundant AC power supplies, 2 * redundant cooling fans, 4 * shortwave SFPs; Includes Sun StorageTek(TM) Common Array Manager software and 2 * storage domains using Sun StorageTek(TM) Storage Domains software; RoHS-5	3 339 100 Ft
XTA2540R01A2F1500	Sun StorageTek(TM) 2540 FC Array, Rack-Ready Controller Tray, 1500GB, 5* 300GB 15Krpm SAS drives, 2 * 512MB cache FC HW RAID controllers, 2 * redundant AC power supplies, 2 * redundant cooling fans, 4 * shortwave SFPs; Includes Sun StorageTek(TM) Common Array Manager software and 2 * storage domains using Sun StorageTek(TM) Storage Domains software; RoHS-5	2 295 700 Ft
SG-XPCI2FC-QF4	Sun Storagetek PCI-X Enterprise 4Gb FC Host Bus Adapter, Dual Port includes standard and low profile brackets. RoHS 6 compliant	456 500 Ft
SG-XPCI2FC-EM4-Z	Sun StorageTek PCI-X Enterprise 4Gb Dual Channel FC Emulex Host Bus Adapter, includes standard and low profile brackets. RoHS 6 compliant	456 500 Ft
SG-XPCI1FC-QF4	Sun Storagetek PCI-X Enterprise 4Gb FC Host Bus Adapter, Single Port includes standard and low profile brackets. RoHS 6 compliant	255 700 Ft
SG-XPCI1FC-EM4-Z	Sun StorageTek PCI-X Enterprise 4Gb FC Host Bus Adapter, Emulex, Single Port includes standard and low profile brackets. RoHS 6 compliant	255 700 Ft
XTA-2500-2URK-19U	Sun StorEdge(TM) 2500 2U universal rack, adjustable depth rail kit; RoHS-5	29 600 Ft
Sun Storage J4200		
XTA4200R00A10DISK	Sun(TM) Storage J4200 array, Rack-Ready Chassis, No drives, 1 * SAS I/O Module, 2 * redundant AC power supplies and 2 * redundant cooling fans; includes 1 * .5m SAS interconnect cable; RoHS-5	289 800 Ft
XTA-4200-2URK-19U	Sun(TM) Storage J4200 2U universal rack rail kit; RoHS-5	24 700 Ft
XTA-4200-IOM	1 * Sun(TM) Storage J4200 SAS I/O module; includes 1 * .5m SAS interconnect cable; RoHS-5	82 800 Ft
SGXPCIESAS-R-EXT-Z	Sun StorageTek (TM) 8-port external SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. X-Option.	90 300 Ft
SG-XPCIE8SAS-E-Z	Sun StorageTek (TM) 8-port external SAS PCI-Express Host Bus Adapter. RoHS 6. X-option	41 900 Ft

Part#	Description	Price
XTA-ST1NJ-250G7K	1 * Internal 250GB 7.2Krpm SATA HDD, 3.5? x 1? drive with bracket for Sun(TM) Storage J4200; RoHS-6	20 300 Ft
XTA-ST1NJ-500G7K	1 * Internal 500GB 7.2Krpm SATA HDD, 3.5? x 1? drive with bracket for Sun(TM) Storage J4200 and J4400; RoHS-6	47 300 Ft
XTA-ST1NJ-1T7K	1 * Internal 1TB 7.2Krpm SATA HDD, 3.5? x 1? drive with bracket for Sun(TM) Storage J4400 and J4200; RoHS-6	62 700 Ft
XTA-SS1NJ-300G15K	1 * Internal 300GB 15Krpm SAS HDD, 3.5" x 1" drive with bracket for Sun(TM) Storage J4200 and J4400; RoHS-6	68 600 Ft
XTA6ST1NJ-1T7K	6 * Internal 1TB 7.2Krpm SATA HDD, 3.5" x 1" drives with brackets for Sun(TM) Storage J4400 and J4200; RoHS-6	307 500 Ft
XTA6ST1NJ-500G7K	6 * Internal 500GB 7.2Krpm SATA HDD, 3.5" x 1" drives with brackets for Sun(TM) Storage J4200 and J4400; RoHS-6	201 100 Ft
Sun Storage J4400		
XTA4400R00A10DISK	Sun(TM) Storage J4400 array, Rack-Ready Chassis, No drives, 1 * SAS I/O Module, 2 * redundant AC power supplies and 2 * redundant cooling fans; includes 1 * .5m SAS interconnect cable; RoHS-5	289 800 Ft
XTA-4200-2URK-19U	Sun(TM) Storage J4400 4U universal rack rail kit; RoHS-5	34 600 Ft
XTA-4400-IOM	1 * Sun(TM) Storage J4400 SAS I/O module; includes 1 * .5m SAS interconnect cable; RoHS-5	104 100 Ft
SGXPCIESAS-R-EXT-Z	Sun StorageTek (TM) 8-port external SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. X-Option.	90 300 Ft
SG-XPCIE8SAS-E-Z	Sun StorageTek (TM) 8-port external SAS PCI-Express Host Bus Adapter. RoHS 6. X-option	41 900 Ft
XTA-ST1NJ-250G7K	1 * Internal 250GB 7.2Krpm SATA HDD, 3.5? x 1? drive with bracket for Sun(TM) Storage J4200; RoHS-6	20 300 Ft
XTA-ST1NJ-500G7K	1 * Internal 500GB 7.2Krpm SATA HDD, 3.5? x 1? drive with bracket for Sun(TM) Storage J4200 and J4400; RoHS-6	47 300 Ft
XTA-ST1NJ-1T7K	1 * Internal 1TB 7.2Krpm SATA HDD, 3.5? x 1? drive with bracket for Sun(TM) Storage J4400 and J4200; RoHS-6	62 700 Ft
XTA-SS1NJ-300G15K	1 * Internal 300GB 15Krpm SAS HDD, 3.5" x 1" drive with bracket for Sun(TM) Storage J4200 and J4400; RoHS-6	68 600 Ft
XTA6ST1NJ-1T7K	6 * Internal 1TB 7.2Krpm SATA HDD, 3.5" x 1" drives with brackets for Sun(TM) Storage J4400 and J4200; RoHS-6	307 500 Ft
XTA6ST1NJ-500G7K	6 * Internal 500GB 7.2Krpm SATA HDD, 3.5" x 1" drives with brackets for Sun(TM) Storage J4200 and J4400; RoHS-6	201 100 Ft

Part#	Description	Price
Sun Storage J4500		
XTA4500R00A1A24TB	Sun(TM) Storage J4500 array, Rack-Ready, 24TB, 48 * 500GB 7.2Krpm SATA drives, 1 * SAS I/O Module, 2 * redundant AC power supplies and 2 * redundant cooling fans; Includes 2 * 2m SAS interconnect cables and 1 * slide rail kit; RoHS-5	5 530 400 Ft
XTA4500R00A1L36TB	Sun(TM) Storage J4500 array, Rack-Ready, 36TB, 48 * 750GB 7.2Krpm SATA drives, 1 * SAS I/O Module, 2 * redundant AC power supplies and 2 * redundant cooling fans; Includes 2 * 2m SAS interconnect cables and 1 * slide rail kit; RoHS-5	7 904 400 Ft
XTA4500R00A1N48TB	Sun(TM) Storage J4500 array, Rack-Ready, 48TB, 48 * 1TB 7.2Krpm SATA drives, 1 * SAS I/O Module, 2 * redundant AC power supplies and 2 * redundant cooling fans; Includes 2 * 2m SAS interconnect cables and 1 * slide rail kit; RoHS-5	11 060 900 Ft
SGXPCIESAS-R-EXT-Z	Sun StorageTek (TM) 8-port external SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. X-Option.	90 300 Ft
SG-XPCIE8SAS-E-Z	Sun StorageTek (TM) 8-port external SAS PCI-Express Host Bus Adapter. RoHS 6. X-option	41 900 Ft
Kipróbálható berendezések (Try&Buy)		

Sun SPARC Enterprise M3000		
SEWPBAA1Z	Sun SPARC Enterprise M3000 server. Includes 1, 2-Core, 2.52GHz SPARC64 VII Processor (1 CPU board with 1, 2 core CPU & 5MB on-chip L2 10-way cache), and 4GB system memory (1 memory module with 4*1GB DDR2 DIMMs), 2 * 146GB SAS hard disks, 1 DVD-ROM, 4*Gb ethernet ports, 1 I/O tray with 4 PCI-E slots, 2 power supplies (110V or 220V with 1N redundancy), RoHS-5.	3 417 400 Ft
SEWPA1Z	Sun SPARC Enterprise M3000 server. Includes 1, (quad-core) 2.52GHz SPARC64 VII Processor (1 CPU board with 1 CPU & 5MB on-chip L2 10-way cache), and 4GB system memory (1 memory module with 4*1GB DDR2 DIMMs), 2 * 146GB SAS hard disks, 1 DVD-ROM, 4*Gb ethernet ports, 1 I/O tray with 4 PCI-E slots, 2 power supplies (110V or 220V with 1N redundancy), RoHS-5.	3 417 400 Ft
SEWPABA1Z	Sun SPARC Enterprise M3000 server. Includes 1, quad-core,2.52GHz SPARC64 VII Processor (1 CPU board with 1 CPU & 5MB on-chip L2 10-way cache), and 8GB system memory (1 memory module with 4*2GB DDR2 DIMMs), 2 * 146GB SAS hard disks, 1 DVD-ROM, 4*Gb ethernet ports, 1 I/O tray with 4 PCI-E slots, 2 power supplies (110V or 220V with 1N redundancy), RoHS-5.	4 356 500 Ft

Part#	Description	Price
SEWPACA1Z	Sun SPARC Enterprise M3000 server. Includes 1, quad-core,2.52GHz SPARC64 VII Processor (1 CPU board with 1 CPU & 5MB on-chip L2 10-way cache), and 16GB system memory (1 memory module with 4*4GB DDR2 DIMMs), 2 * 146GB SAS hard disks, 1 DVD-ROM, 4*Gb ethernet ports, 1 I/O tray with 4 PCI-E slots, 2 power supplies (110V or 220V with 1N redundancy), RoHS-5.	6 208 700 Ft
SEWPADA1Z	Sun SPARC Enterprise M3000 server. Includes 1, 4 core, 2.52GHz SPARC64 VII Processor (1 CPU board with 1, 4 core CPU & 5MB on-chip L2 10-way cache), and 32GB system memory (1 memory module with 4*8GB DDR2 DIMMs), 2 * 146GB SAS hard disks, 1 DVD-ROM, 4*Gb ethernet ports, 1 I/O tray with 4 PCI-E slots, 2 power supplies (110V or 220V with 1N redundancy), RoHS-5.	9 913 100 Ft